

Koła pasowe calowe pod Taper Lock

Koła pasowe 1/2" (12.70mm) H300

Ilość zębów	Typ	Taper Lock	De	Dp	Df	Dm	Di	F	S	R	Kg
20	4FB	1615	79.48	80.85	87	-	65	84	38	23.0	1.5
21	4FB	1615	83.52	84.89	91	-	66	84	38	23.0	12.0
22	4FB	1615	87.56	88.94	94	-	67	84	38	23.0	1.6
23	4FB	1615	91.61	92.98	102	-	71	84	38	23.0	1.8
24	4FB	1615	95.65	97.02	102	-	75	84	38	23.0	2.1
25	4FB	1615	99.69	101.06	112	-	79	84	38	23.0	2.0
26	4FB	1615	103.73	105.11	112	-	83	84	38	23.0	2.7
27	4FB	2012	107.78	109.15	120	-	87	84	32	26.0	3.0
28	4FB	2012	111.82	113.19	120	-	91	84	32	26.0	2.4
30	4FB	2012	119.90	121.28	128	-	99	84	32	26.0	2.9
32	4FB	2517	127.99	129.36	135	-	107	84	45	19.5	3.3
36	4FB	2517	144.16	145.53	158	-	124	84	45	19.5	4.5
40	4FB	2517	160.33	161.70	168	-	137	84	45	19.5	6.0
44	4FW	2517	176.50	177.87	184	119	153	86	45	20.5	6.5
48	4FW	2517	192.67	194.04	200	119	169	86	45	20.5	7.6
60	9A	2517	241.18	242.55	-	119	223	86	45	20.5	8.4
72	9A	2517	289.69	291.06	-	119	270	86	45	20.5	10.4
84	9A	2517	338.20	339.57	-	119	320	86	45	20.5	12.5
96	9A	3030	386.71	338.08	-	150	362	86	76	5.0	14.2
120	9A	3030	483.73	485.10	-	150	460	86	76	5.0	18.8

