

Koła zębate Metryczne typ AT



Podziałka = 5mm szer. pasa = 10mm **21 AT5**

Z	Typ	De	Df	Dm	F	L	d	kg
12	6F	17.85	23.0	11.0	15.0	21	4	0.018
14	6F	21.05	25.0	14.0	15.0	21	4	0.019
15	6F	22.65	28.0	16.0	15.0	21	6	0.021
16	6F	24.20	32.0	18.0	15.0	21	6	0.025
18	6F	27.40	32.0	20.0	15.0	21	6	0.031
19	6F	29.00	36.0	22.0	15.0	21	6	0.036
20	6F	30.60	36.0	23.0	15.0	21	6	0.038
22	6F	33.85	38.0	24.0	15.0	21	6	0.046
24	6F	37.00	42.0	26.0	15.0	21	6	0.054
25	6F	38.60	44.0	26.0	15.0	21	6	0.058
26	6F	40.20	44.0	26.0	15.0	21	6	0.061
27	6F	41.80	48.0	30.0	15.0	21	8	0.064
28	6F	43.35	48.0	32.0	15.0	21	8	0.068
30	6F	46.55	51.0	34.0	15.0	21	8	0.075
32	6F	49.70	54.0	36.0	15.0	21	8	0.088
36	6F	56.05	63.0	38.0	15.0	21	8	0.114
40	6F	62.45	66.0	40.0	15.0	21	8	0.138
42	6F	65.60	70.0	40.0	15.0	21	8	0.160
44	6	68.80	-	45.0	15.0	21	8	0.174
48	6	75.15	-	50.0	15.0	21	8	0.200
60	6	94.25	-	65.0	15.0	21	8	0.307

Materiał: aluminium 6082 T6 UNI 9006/4

Podziałka = 5mm szer. pasa = 16mm **27 AT5**

Z	Typ	De	Df	Dm	F	L	d	kg
12	6F	17.85	23.0	11.0	21.0	27	4	0.022
14	6F	21.05	25.0	14.0	21.0	27	4	0.026
15	6F	22.65	28.0	16.0	21.0	27	6	0.029
16	6F	24.20	32.0	18.0	21.0	27	6	0.035
18	6F	27.40	32.0	20.0	21.0	27	6	0.043
19	6F	29.00	36.0	22.0	21.0	27	6	0.049
20	6F	30.60	36.0	23.0	21.0	27	6	0.053
22	6F	33.85	38.0	24.0	21.0	27	6	0.065
24	6F	37.00	42.0	26.0	21.0	27	6	0.076
25	6F	38.60	44.0	26.0	21.0	27	6	0.082
26	6F	40.20	44.0	26.0	21.0	27	6	0.085
27	6F	41.80	48.0	30.0	21.0	27	8	0.090
28	6F	43.35	48.0	32.0	21.0	27	8	0.098
30	6F	46.55	51.0	34.0	21.0	27	8	0.105
32	6F	49.70	54.0	36.0	21.0	27	8	0.123
36	6F	56.05	63.0	38.0	21.0	27	8	0.160
40	6F	62.45	66.0	40.0	21.0	27	8	0.193
42	6F	65.60	70.0	40.0	21.0	27	8	0.215
44	6	68.80	-	45.0	21.0	27	8	0.234
48	6	75.15	-	50.0	21.0	27	8	0.280
60	6	94.25	-	65.0	21.0	27	8	0.430

Materiał: aluminium 6082 T6 UNI 9006/4

Podziałka = 5mm szer. pasa = 25mm **36 AT5**

Z	Typ	De	Df	Dm	F	L	d	kg
12	6F	17.85	23.0	11.0	30.0	36	4	0.031
14	6F	21.05	25.0	14.0	30.0	36	4	0.037
15	6F	22.65	28.0	16.0	30.0	36	6	0.041
16	6F	24.20	32.0	18.0	30.0	36	6	0.050
18	6F	27.40	32.0	20.0	30.0	36	6	0.061
19	6F	29.00	36.0	22.0	30.0	36	6	0.070
20	6F	30.60	36.0	23.0	30.0	36	6	0.076
22	6F	33.85	38.0	24.0	30.0	36	6	0.090
24	6F	37.00	42.0	26.0	30.0	36	6	0.109
25	6F	38.60	44.0	26.0	30.0	36	6	0.116
26	6F	40.20	44.0	26.0	30.0	36	6	0.124
27	6F	41.80	48.0	30.0	30.0	36	8	0.128
28	6F	43.35	48.0	32.0	30.0	36	8	0.140
30	6F	46.55	51.0	34.0	30.0	36	8	0.150
32	6F	49.70	54.0	38.0	30.0	36	8	0.176
36	6F	56.05	63.0	38.0	30.0	36	8	0.230
40	6F	62.45	66.0	40.0	30.0	36	8	0.276
42	6F	65.60	71.0	40.0	30.0	36	8	0.310
44	6	68.80	-	45.0	30.0	36	8	0.344
48	6	75.15	-	50.0	30.0	36	8	0.400
60	6	94.25	-	65.0	30.0	36	8	0.614

Materiał: aluminium 6082 T6 UNI 9006/4

