

## Tuleja Mocująca BK15

Wymiary						moment przenoszony Mt Nm	nacisk powierzchniowy wał piasta		śruby zaciskowe			
Ød mm	ØD mm	L <sub>1</sub> mm	L <sub>2</sub> mm	L <sub>3</sub> mm	L mm		P N/mm <sup>2</sup>	P <sub>1</sub> N/mm <sup>2</sup>	liczba	rozmiar	siła dociągu Nm	
14	55	62	17	22	31	39	282	458	118	4	M8x25	41
16	55	62	17	22	31	39	313	400	118	4	M8x25	41
18	55	62	17	22	31	39	353	356	118	4	M8x25	41
19	55	62	17	22	31	39	372	337	118	4	M8x25	41
20	55	62	17	22	31	39	392	320	118	4	M8x25	41
22	55	62	17	22	31	39	431	290	118	4	M8x25	41
24	55	62	17	22	31	39	470	265	118	4	M8x25	41
25	55	62	17	22	31	39	490	255	118	4	M8x25	41
28	55	62	17	22	31	39	549	228	118	4	M8x25	41
30	55	62	17	22	31	39	588	213	118	4	M8x25	41
24	65	72	17	22	31	39	617	332	122	5	M8x25	41
25	65	72	17	22	31	39	637	320	122	5	M8x25	41
28	65	72	17	22	31	39	725	285	122	5	M8x25	41
30	65	72	17	22	31	39	764	267	122	5	M8x25	41
32	65	72	17	22	31	39	823	250	122	5	M8x25	41
35	65	72	17	22	31	39	902	228	122	5	M8x25	41
38	65	72	17	22	31	39	970	210	122	5	M8x25	41
40	65	72	17	22	31	39	1029	200	122	5	M8x25	41
30	80	87	20	25	33	41	1082	315	120	7	M8x25	41
32	80	87	20	25	33	41	1155	298	120	7	M8x25	41
35	80	87	20	25	33	41	1260	272	120	7	M8x25	41
38	80	87	20	25	33	41	1370	250	120	7	M8x25	41
40	80	87	20	25	33	41	1440	238	120	7	M8x25	41
42	80	87	20	25	33	41	1510	226	120	7	M8x25	41
45	80	87	20	25	33	41	1620	212	120	7	M8x25	41
48	80	87	20	25	33	41	1735	198	120	7	M8x25	41
50	80	87	20	25	33	41	1806	190	120	7	M8x25	41

### TULEJA BK15

tolerancje  
d:- h8  
D:- H8  
Samocentrująca

