

Tuleja BK25

Wymiary					Moment Przenoszony		Nacisk powierzchniowy Shaft Hub		Śruby montażowe		
Ød mm	ØD mm	ØD ₁ mm	L ₁ mm	L mm	Mt Nm	Ft kN	P N/mm ²	P ₁ N/mm ²	ilość	Size	T _s Nm
14	25	32	20	30	91	13	124	74	1	M20x1	92
15	25	32	20	30	99	13	117	70	1	M20x1	92
16	25	32	20	30	80	10	83	53	1	M20x1	70
17	25	32	20	32	99	12	91	62	1	M22x1.5	91
18	30	32	20	32	193	21	158	95	1	M25x1.5	188
19	30	38	20	32	167	18	123	78	1	M25x1.5	154
20	30	38	20	32	136	14	90	60	1	M25x1.5	119
22	35	45	25	36	345	31	151	95	1	M30x1.5	327
24	35	45	25	36	262	22	96	66	1	M30x1.5	228
25	35	45	25	36	209	17	71	51	1	M30x1.5	175
28	40	52	25	37	447	32	121	85	1	M35x1.5	387
30	40	52	25	37	298	20	70	53	1	M35x1.5	242
32	45	52	30	44	701	44	121	86	1	M40x1.5	606
35	45	58	30	44	403	23	58	45	1	M40x1.5	319
36	50	58	30	45	283	16	39	28	1	M40x1.5	217
38	50	58	30	45	805	42	99	75	1	M45x1.5	657
40	50	65	30	45	524	26	58	46	1	M45x1.5	407
42	55	65	30	46	1184	56	119	91	1	M50x1.5	966
45	55	70	30	46	661	29	58	47	1	M50x1.5	503
48	60	75	30	46	1267	53	97	78	1	M55x2	1000
50	60	75	30	46	813	33	58	48	1	M55x2	616
55	65	80	30	46	768	28	45	38	1	M60x2	574
60	70	85	30	52	1420	47	70	60	1	M65x2	1045

Tuleja BK 25

Tolerancje:
d- h8
D:- H8
samocentrująca

