

Tuleja Mocująca BK40

Wymiary					moment przenoszony		nacisk powierzchniowy		śruby zaciskowe (DIN 912-12.9)		
Ød mm	ØD mm	L ₁ mm	L ₂ mm	L mm	Mt Nm	Ft kN	P N/mm ²	P ₁ N/mm ²	liczba	rozmiar	siła dociągu Nm
19	47	17	20	26	270	26.8	220	93	8	M6x18	16
20	47	17	20	26	280	26.8	210	93	8	M6x18	16
22	47	17	20	26	315	26.8	207	96	8	M6x18	16
24	50	17	20	26	375	30.1	206	103	9	M6x18	16
25	50	17	20	26	390	30.1	206	103	9	M6x18	16
28	55	17	20	26	485	33.5	204	103	10	M6x18	16
30	55	17	20	26	520	33.5	190	103	10	M6x18	16
32	60	17	20	26	660	40.2	214	114	12	M6x18	16
35	60	17	20	26	715	40.2	196	114	12	M6x18	16
38	65	17	20	26	920	46.9	204	122	14	M6x18	16
40	65	17	20	26	960	46.9	200	122	14	M6x18	16
42	75	20	24	32	1550	73.2	228	125	12	M8x22	38
45	75	20	24	32	1650	73.2	208	125	12	M8x22	38
48	80	20	24	32	1756	73.2	190	110	12	M8x22	38
50	80	20	24	32	1830	73.2	189	115	12	M8x22	38
55	85	20	24	32	2348	85.4	200	130	14	M8x22	38
60	90	20	24	32	2580	85.4	180	122	14	M8x22	38
65	95	20	24	32	3190	97.6	191	130	16	M8x22	38
70	110	24	28	38	4800	134.4	211	132	14	M10x25	75
75	115	24	28	38	5100	134.4	194	128	14	M10x25	75
80	120	24	28	38	5400	134.4	182	124	14	M10x25	75
85	125	24	28	38	6500	153.6	196	133	16	M10x25	75
90	130	24	28	38	6920	153.6	181	128	16	M10x25	75
95	135	24	28	38	8350	172.8	196	139	18	M10x25	75
100	145	26	33	45	9970	197.4	198	139	14	M12x30	130
110	155	26	33	45	11050	187.4	181	128	14	M12x30	130
120	165	26	33	45	13600	225.6	187	139	16	M12x30	130
130	180	34	38	50	18500	282.0	168	119	20	M12x35	130
140	190	34	38	50	21700	310.1	168	128	22	M12x35	130
150	200	34	38	50	25300	338.4	170	128	24	M12x35	130
160	210	34	38	50	29300	366.6	171	132	26	M12x35	130
170	225	38	44	58	33300	389.0	162	123	22	M14x40	207
180	235	38	44	58	38600	424.0	168	128	24	M14x40	207
190	250	46	52	66	47150	495.0	154	114	28	M14x45	207
200	260	46	52	66	53800	531.0	157	118	30	M14x45	207

Tuleja mocująca BK40

Tolerancja:
d:- h8
D:- H8
Nie samocentryczna

