

## Tuleja mocująca BK50

Wymiary				Moment przenoszony			Nacisk pow.	
Ød mm	ØD mm	L mm	L <sub>1</sub> mm	Mt Nm	Fa kN	Ft kN	wał P N/mm <sup>2</sup>	piasta P <sub>1</sub> N/mm <sup>2</sup>
8	11	4.5	3.7	2.9	4.3	0.97	98	73
10	13	4.5	3.7	6.9	12.1	1.37	98	75
12	15	4.5	3.7	9.8	12.4	1.64	98	78
14	18	6.3	5.3	19.2	20.4	2.74	98	76
15	19	6.3	5.3	22.1	23.5	2.94	98	77
16	20	6.3	5.3	25.1	23.9	3.14	98	78
18	22	6.3	5.3	31.8	24.8	3.53	98	80
19	24	6.3	5.3	35.3	29.1	3.72	98	77
20	25	6.3	5.3	39.2	29.5	3.92	98	78
22	26	6.3	5.3	47.0	28.3	4.31	98	83
24	28	6.3	5.3	56.8	29.4	4.70	98	84
25	30	6.3	5.3	60.8	31.8	4.90	98	81
28	32	6.3	5.3	76.4	31.9	5.49	98	86
30	35	6.3	5.3	88.2	34.8	5.88	98	84
32	36	6.3	5.3	100.0	35.9	6.27	98	87
35	40	7.0	6.0	136.0	44.8	7.74	98	86
38	44	7.0	6.0	160.0	48.8	8.43	98	84
40	45	8.0	6.6	195.0	57.6	9.75	98	87
42	48	8.0	6.6	216.0	61.4	10.30	98	86
45	52	10.0	8.6	321.0	90.3	14.30	98	85
48	55	10.0	8.6	367.0	92.7	15.30	98	85
50	57	10.0	8.6	397.0	94.7	15.90	98	86
55	62	10.0	8.6	480.0	99.7	17.40	98	87
60	68	12.0	10.4	692.0	130.9	23.00	98	86
65	73	12.0	10.4	813.0	134.9	25.00	98	87
70	79	14.0	12.2	1110.0	172.4	31.60	98	87
75	84	14.0	12.2	1260.0	185.7	33.80	98	87
80	91	17.0	15.0	1770.0	247.1	44.10	98	86
90	101	17.0	15.0	2240.0	266.2	50.00	98	87
100	114	21.0	18.7	3450.0	370.8	69.60	98	86
110	124	21.0	18.7	4170.0	406.1	76.40	98	87
120	134	21.0	18.7	4950.0	432.0	83.30	98	88
130	148	28.0	25.3	7840.0	640.8	122.00	98	86
140	158	28.0	25.3	9110.0	676.5	131.00	98	87
150	168	28.0	25.3	10500.0	713.0	140.00	98	87

Tuleja mocująca BK50

Tolerancje  
do śr. 40mm  
d:- h6  
D:- H7  
powyżej 40mm  
d:- h8  
D:- H8  
Nie samocentrująca

